



DUCHESNE

Solidly Dependable®

Self-serve sales center CONSTRUCTION NAILS

INDOOR
only



Bright

Natural finish
No protection against corrosion

Electro-galvanized

Zinc coating applied through electrolysis
Minimum protection against corrosion

Blued

Increases the visibility of the nail in the gypsum
No protection against corrosion

Phosphate coated

Increases the holding power of the nail
No protection against corrosion

OUTDOOR

compatible with ACQ
pressure-treated lumber



Hot galvanized

Zinc coating applied through
galvanization process
Superior protection against corrosion

Stainless steel

Corrosion resistant material
Optimum protection against corrosion

General construction & framing

COMMON
¾" to 14"



AVAILABLE FINISHES



APPLICATIONS

- ▶ General construction
- ▶ Woodworking
- ▶ Framing
- ▶ Treated lumber patio decks and fences

REGULAR ARDOX
1" to 12"

Increases holding power
Reduces wood splitting



AVAILABLE FINISHES



APPLICATIONS

- ▶ General construction
- ▶ Woodworking
- ▶ Framing
- ▶ Treated lumber patio decks and fences

BOX
1" to 6"

Thinner shank
Reduces wood splitting



AVAILABLE FINISHES



APPLICATIONS

- ▶ General construction
- ▶ Woodworking
- ▶ Framing
- ▶ Treated lumber patio decks and fences

Finishing

FINISHING
¾" to 4"



AVAILABLE FINISHES




APPLICATIONS

- ▶ Mouldings
- ▶ Trims
- ▶ For finishing work where nail head must be concealed

FINISHING ARDOX
1¼" to 4"

Increases holding power
Reduces wood splitting



AVAILABLE FINISHES




APPLICATIONS

- ▶ Mouldings
- ▶ Trims
- ▶ For finishing work where nail head must be concealed

Roofing

ROOFING
⅞" to 3½"

10ga. & 11ga.



AVAILABLE FINISHES



APPLICATIONS

- ▶ Asphalt shingles
- ▶ Felt paper
- ▶ Sheathing
- ▶ Vinyl siding

Concrete

CONCRETE (HEAT TREATED)
½" to 5"



AVAILABLE FINISHES




APPLICATION

- ▶ Fastening into masonry

Stainless steel

STAINLESS STEEL
1½" to 3½"



AVAILABLE FINISH



APPLICATIONS

- ▶ Outdoor projects, treated lumber patio decks and fences
- ▶ For projects where rust and corrosion are not permitted

Specific uses

RINGED DRYWALL
1¼" to 2"



AVAILABLE FINISHES



APPLICATION

- ▶ For gypsum board (drywall) installation

OVAL HEAD SIDING
2" to 3"



AVAILABLE FINISH



APPLICATION

- ▶ For clapboard installation

RINGED UNDERLAY FLOORING 12.5ga. & 14ga.
1¼" to 1¾"



AVAILABLE FINISH



APPLICATION

- ▶ For underlay installation

ARDOX FLOORING (HEAT TREATED)
2" to 2½"



AVAILABLE FINISH



APPLICATION

- ▶ For hardwood floor installation

HARDWOOD FLOORING FINISHING (HEAT TREATED)
1¾"



AVAILABLE FINISH



APPLICATIONS

- ▶ Beginning and end of hardwood floor installations

DOUBLE-HEADED
1¼" to 4"



AVAILABLE FINISH



APPLICATIONS

- ▶ For temporary use and formwork

STAPLES
¾" to 2"



AVAILABLE FINISHES



APPLICATIONS

- ▶ For the installation of fences, mesh, netting, wires

PLASTIC CAP
2" to 3"



AVAILABLE FINISH



APPLICATION

- ▶ For the installation of insulating sheathing

ALUMINUM
1" to 3"



AVAILABLE FINISHES



APPLICATIONS

- ▶ For cladding, soffit, etc.

PANELING NAILS
1" & 1½"




AVAILABLE FINISHES



APPLICATIONS

- ▶ For the installation of interior prefinished paneling and mouldings

JOIST HANGER
1¼" to 2½"



AVAILABLE FINISHES



APPLICATION

- ▶ For the installation of joist hangers to wood

* For other types, lengths and sizes of Duchesne nails, please verify availability with your dealer.